



## PoE 10/100M x 16 + gigabit/SFP x 2 16-ch PoE Unmanaged Network Switch

### Features

- IEEE 802.3af / 802.3at
- Fully compatible with WAMA IP-based products
- Plug-and-Play – zero configuration
- 220W for powering IP cameras
- 19" rack-mountable design

### Specifications

Model	CO-16ES2
Pass Through Data Rates	16-Port 10/100Mbps; 2-Port (Gigabit / SFP) 10/100/1000Mbps
PoE Standard	IEEE 802.3af, IEEE 802.3at (PoE+)
LED	Power (Green) PoE In-use (Orange) 10/100 LNK / ACT (Green)
PoE Power Output	54V DC, 560mA, max. 30W per port, 220W (Total)
PoE Power Supply Type	1/2(+), 3/6(-), Mode-A, End-Span
Power Requirement	100 ~ 240V AC, 50-60Hz, 250W (Max.)
Storage Environment	-10°C ~ 55°C / 20 - 90% humidity (non-condensing)
Operating Environment	0°C ~ 40°C / 20 - 90% humidity (non-condensing)
Dimension (mm)	440 (W) x 208 (D) x 44 (H)
Weight	4 kg



#### WAMA Technology Limited

Unit 502, 5/F, Block B, Wing Kut Industrial Building,  
608 Castle Peak Road, Kowloon, Hong Kong.

Tel : (852) 3703 9260

Email : info@wamatech.co

Fax : (852) 3705 0053

Website : www.wamatech.co