





Intelligent 2MP Mini Eyeball IP Camera

Features

- Sony 1/2.9" 2.1MP CMOS sensor
- H.265 / H.264 dual streams
- Built-in video analytic functions
- Day/Night (ICR), WDR, 3DNR, AGC
- Motion detection
- Privacy masks
- ONVIF (Profile S)
- Power over Ethernet (PoE)



Dimensions



Specifications

Model	NM2-D22W
CAMERA	
Image Sensor	Sony 1/2.9" 2.1MP CMOS sensor
Effective Pixel	1920 (H) x 1080 (V)
Frame Rate	25/30fps
Resolution	Up to 1080p (main stream); up to D1 (sub stream)
Video Compression	H.265 / H.264 (16kbps – 8000kbps)
Audio Compression	-
Open Standard	ONVIF (Profile S)
Min. Illumination	0.0 lux (IR on)
IR Range	15m
Sync System	Internal
Scan System	Progressive scan
Lens	2.8mm
Angle of View	Horizontal: 102°; Vertical: 57°
Electronic Shutter	Auto / manual (1/30-1/10000) / FLK
S/N Ratio	≥50db
CONTROL	
Video Adjustment	Brightness, contrast, saturation, sharpness, hue
3D Noise Reduction	Close / low / mid / mid-high / high
Digital WDR	Close / low / mid / high
Auto Gain Control	Low / mid-low / mid / mid-high / high
Day / Night	Auto / color / B/W / external
Privacy Mask	4 zones
Mirror	Close / horizontal / vertical / 90° rotation / 180° rotation / 270° rotation
Defogging	Close / low / mid / high
EVENT	
Event Type	Video motion detection, video tamper
Video Analysis	Tripwire, loitering, missing / unattended object detection, crowd monitoring
Action Type	Dial-back, snapshot, email notification
External Alarm Input	0
Motion Detection	4
Relay Output	0
COMMUNICATION	
Network	RJ-45, 100 base-T
Protocol	TCP/IP, UDP, HTTP, DHCP, RTSP, DDNS, SMTP(SSL), PPPoE, UPNP, NTP, P2P, FTP
Concurrent Connection	3
Audio Input	0
Audio Output	0
Video Output	0
MISCELLANEOUS	
Weather Protection	IP66
Operating Environment	-20 ~ 55°C / 90% relative humidity (no condensation)
Power Supply	DC12V / PoE, 6W
Dimensions (mm)	75 (H) x Φ93 (D)
Weight	400g



WAMA Technology Limited

Unit 502, 5/F, Block B, Wing Kut Industrial Building,

608 Castle Peak Road, Kowloon, Hong Kong.

Tel : (852) 3703 9260

Email : info@wamatech.co

Fax : (852) 3705 0053

Website : www.wamatech.co