






2MP H.264 10x IR High Speed Dome IP Camera

Features

- 1/2.8" 2.0MP CMOS sensor
- 10X optical zoom
- H.264 / M-JPEG dual streams
- Micro SD slot for recording
- Enhancements: D-WDR, 3D NR
- ONVIF (Profile S)



Dimensions



Specifications

Model	NZ2-T310
CAMERA	
Image Sensor	1/2.8" 2.0MP CMOS sensor
Effective Pixel	1920 (H) x 1080 (V)
Frame Rate	25/30fps
Resolution	up to 1920 x 1080 (main stream); up to D1 (sub stream)
Video Compression	H.264, M-JPEG (100kbps – 6000kbps)
Open Standard	ONVIF (Profile S)
Min. Illumination	0.0 lux (IR on); 0.06 lux (colour, IR off), 0.01 lux (B/W, IR off)
IR Range	80m
Lens	10X optical zoom, f=4.7–47mm
Electronic Shutter	1/15 (Max) ; 1/5000 (Min)
S/N Ratio	≥50db
CONTROL	
Video Adjustment	Brightness, contrast, sharpness
Noise Reduction	3D NR
Digital WDR	1 - 5 / off
Video Compensation	BLC / HLC / off
Auto Gain Control	Auto / on / off
Day / Night Mode	Auto / day / night
TELEMETRY	
Panning Angle	360°
Panning Speed	0.1°-200°/sec (manual); 240°/sec (preset)
Tilting Angle	90°
Preset	255
Patrol	4
Tour	4
Pattern	4
Home Position	Preset / patrol / tour / pattern / off
EVENT	
Event Type	External alarm, video motion detection
Action Type	Dial-back, relay switch control, email notification, micro SD card recording
External Alarm Input	1
Motion Detection	4
Relay Output	1
COMMUNICATION	
Network	RJ-45, 100 base-T
Protocol	TCP/IP, UDP, HTTP, DHCP, RTSP, DDNS, SMTP(SSL), PPPoE, UPNP, NTP, P2P, FTP
Concurrent Connection	5
Audio Input	1
Audio Output	1
Video Output	1 (CVBS)
MISCELLANEOUS	
Operating Environment	-20 ~ 55°C / 90% relative humidity (no condensation)
Power Supply	AC24V, DC24V/PoE (IEEE802.3at), 25W
Dimensions (mm)	291 (H) x Φ149 (D)
Weight	2.7kg

