





2MP Human & Vehicle AI Bullet IP Camera

Features

- Sony 1/2.8" 2MP CMOS sensor
- Deep learning technology for recognizing human/vehicle
- Support people/vehicle counting, retrograde detection, intrusion detection & absence detection functions
- Support statistical reports
- H.265 / H.264 / M-JPEG dual streams
- Motorized vari-focal lens
- Micro SD slot for recording
- ONVIF (Profile S)
- Power over Ethernet (PoE)



Dimensions



Specifications

Model	VS2-B36W
CAMERA	
Image Sensor	Sony 1/2.8" 2MP CMOS sensor
Effective Pixel	1920 (H) x 1080 (V)
Frame Rate	25/30fps
Resolution	Up to 1080p (main stream); up to D1 (sub stream)
Video Compression	H.265 / H.264 (16kbps – 8000kbps)
Audio Compression	G.711u (64kbps)
Open Standard	ONVIF (Profile S)
Min. Illumination	0.0 lux (IR on)
IR Range	40m
Sync System	Internal
Scan System	Progressive scan
Lens	2.8 - 12mm motorized lens
Electronic Shutter	Auto / manual (1/5-1/100000) / FLK
S/N Ratio	≥50db (AGC off)
CONTROL	
Video Adjustment	Brightness, contrast, saturation, sharpness, hue
3D Noise Reduction	Close / low / mid / mid-high / high
True WDR	Close / low / mid / high
Auto Gain Control	Low / mid-low / mid / mid-high / high
Day / Night	Auto / color / B/W / external
Privacy Mask	4 zones
Mirror	Close / horizontal / vertical / 90° rotation / 180° rotation / 270° rotation
Slow Shutter	Close / open
EVENT	
Event Type	External alarm, video motion detection, video tamper, network interruption
Video Analysis	People/vehicle counting & statistical reporting (with micro SD card), retrograde detection, intrusion detection, absence detection
Action Type	Dial-back, snapshot, relay switch control, email notification, micro SD card recording
External Alarm Input	2
Motion Detection	4
Relay Output	1
COMMUNICATION	
Network	RJ-45, 100 base-T
Protocol	TCP/IP, UDP, HTTP, HTTPS, DHCP, RTSP, DDNS, SMTP(SSL), PPPoE, UPNP, NTP, P2P, FTP
Concurrent Connection	4
Audio Input	1
Audio Output	1
Video Output	0
MISCELLANEOUS	
Weather Protection	IP66
Operating Environment	-20 ~ 55°C / 90% relative humidity (no condensation)
Power Supply	DC12V / PoE, 10W
Dimensions (mm)	93 (W) x 96 (H) x 263 (L)
Weight	904g

